I. Specifications:

Working temperature: -20-60 °C

Supply voltage: DC12-24V

External dimension:L876xW876xH41mm

Function: adjusting light Max load current: 16A

II. Attentions:

- 1. Supply voltage of this product is DC12-24V; It is forbidden for others
- Load wire should be connected correctly according to colors that connect drawing offers.
- Warranty of this product is one year, in this period we guarantee replacement or repairing with no charge, but exclude the artificial damage or overloadworking.

III.Control method:

Adopt IR remoter to control the dimmer, which has 12 buttons, the function of each button as below:

symbol	Name of key	Instruction
(1)	ON/OFF	in any state you could turn on/off dimmer at any times
OFF OFF	DELAY	When put this button, the dimmer will turn off in 30 seconds
() ()	BRIGHTNESS- BRIGHTNESS+	Adjusting brightness button,the brightness progression will add/subtract one when you press the button each time
25% 75%	HOTKEY	Choose different scale of brightness
1 3 2 4	SCENE	If the current brightness is what you want, you can put this button always, until more than 3 seconds; then the light will flicker one times, which explains that the current brightness have been saved When the time you put this button is less than 3 seconds, the brightness, which had been saved in previous time will shich had been saved in previous time will shich had been saved in previous time will show the had been saved in previous time will show the had been saved in previous time will show the had been saved in previous time will show the had been saved in previous time will show the had been saved in previous time will show the had been saved in previous time will show the had been saved in previous time will show the had been saved to be the had been saved to be a saved to be the had been saved to be t

V.Connect Diagram

